

Dealer	Name:	hillside honda	
Dealer #:	206788		

Vehicle Information

 Year:
 2015
 Model:
 CR-V
 VIN:
 2HKRM4H5XFH673991

 Mileage:
 79582
 Color:
 BASQUE RED PEARL II

 Stock #:
 U2513779
 Repair Order #:
 253596E





VIN Verification		Eligible	Not Eligible	VEHICLES REPORTED WITH THE FOLLOWING ARE NOT ELIGIBLE FOR CERTIFICA	ATION
1. Vehicle History Report (VHR cannot have any conditions listed on the	right	:) 0	0	- Odometer Rollback - Hail/Fire/Flood Damage	
2. VIN Status Inquiry (All open campaigns/recalls must be completed))	0	0	- Not Actual Mileage - Dismantled/Reconstructed	
3. VIN Plates (All VIN plates must match engine compartment,				- Exceeds Mechanical Limits - Branded/Junked/Salvaged Title	
doorjamb and dash)		0	0	- Manufacturer Buyback - Airbag Deployment/Gray Market	
Unibody		Eligible	Not Eligible	VEHICLES WITH UNIBODY DAMAGE ARE NOT ELIGIBLE FOR CERTIFICATION:	
4. Frame (Carefully inspect the vehicle for any prior structural damage	e)	0	0	Report any visible signs of unibody damage to the Service Manager.	
Vehicle Diagnostics			Not	VEHICLES WITH AFTER-MARKET ITEMS ARE NOT ELIGIBLE FOR CERTIFICATIO	
5. Check for Diagnostic Trouble Codes (DTC)		Eligible	Eligible		
5. Check for Diagnostic frouble Codes (DTC)		. U	0	Refer to the certified program standards on page 4 of this checklist.	
Front Interior MEETS STANDARDS:	YES N	IO N/A	Re	ear Interior MEETS STANDARDS: YES	NO N/A
6. Key Remotes, at least one (Unlock, lock and panic buttons)	0 (0	40	. Seats (Upholstery condition, operation and tracks)	0 0
7. Keyless Entry System (Driver's-door button-unlock/lock)				. Seat Belts (Belts, buckles, latches, anchors and retraction)	
8. SRS Airbags (Exterior condition/Check warning lamp self-check)	0 (-	42	. Head Restraints (Present & Adjustable up/down)	0 0
9. Ignition Switch/Engine Start Button (Engine starts)	0 0	0		. Windows (Operation-noise, speed, full travel and glass)	O O
10. Instrument Panel Operation (Temp, fuel, speedometer gauge/All			44	. Rear/Sliding Doors (Operation, trim, panels, handles, latches,	
indicators illuminate "ON" position)				locks)	0 0
11. Dash (Condition, instrument panel, light and brightness)	0 0	0	45	. Cargo Light (Condition and operation) $\ \square$	0 0
12. Horn (Operation)					$\overline{}$
13. Steering Wheel (Condition, tilt, telescopic and lock mode)			C	Comments:	
14. Steering Wheel-Mounted Controls (Operation)					
15. Windshield Wipers/Washers (Aim, pressure–front/rear)					
16. Shifter (Check all shifting points–MT or AT)			_		
18. Hood Release (Operation)		0	Е.	and Francisco	
19. Trunk/Tailgate/Hatch Release (Operation)				ont Exterior MEETS STANDARDS: YES	
20. Fuel Door Release (Operation)				. Windshield Glass (Cracks, chips, pits, scratches, antenna)	O O
21. Seats (Operation and tracks)			47.	. Windshield Wiper Blades/Arms (Condition and high-/low-speed	
22. Seat Heaters (Operation and heating performance)				operation)	
23. Seat Belts (Belts, buckles, latches and retraction)	0 (o		Headlights/Lenses (Condition and operation-moisture)	
24. Head Restraints (Present & Adjustable up/down)				Fog Lights/Lenses (Condition and operation)	
25. Windows (Operation-noise, speed, full travel and glass)				Daytime Running Lights/Lenses (Condition and operation)	
26. Front Doors (Operation, trim, panels, handles, latches, locks)	0 0	-	51.	. Turn Signal Lights/Lenses (Condition and operation)	0 0
27. Side Mirrors (Condition, operation, side-view camera–					$\overline{}$
if applicable)			C	Comments:	
28. Rearview Mirror (Operation, auto-dimming-if equipped)					
29. Sunroof/Shade/Glass (Condition and operation)					
30. Sun Visors/Mirrors (Condition-flip up, down/sideways)			_		
31. Interior Lights (Condition and operation)			D	ear Exterior MEETS STANDARDS: YES	
33. Audio System AM/FM/SXM/CD Radio (Operation, display, control	0 (<u>,</u> 0	κe	EAT EXTERIOR MEETS STANDARDS: YES	NO N/A
panel, speakers)	0.0				0 0
34. Intelligent Multi-Information Display (Operation and display)				. Windshield Wiper Blade/Arm (Condition and operation)	0 0
35. Bluetooth* HandsFreeLink* (Perform voice commands—must pair					0 0
with phone)	0 0	0		. Taillights/Lenses (Condition and operation-moisture)	
36. Navigation System (Operation, display, clear all stored data)			56	Backup Lights/Lenses (Condition and operation)	0 0
37. Rearview Camera (Operation and display)			57.	. Turn Signal Lights/Lenses (Condition and operation)	0 0
38. Alarm/Theft-Deterrent System	0 (o	58	Emergency Lights/Lenses (Condition and operation)	0 0
39. Cigarette Lighter/Power Outlets (if equipped)	0 0	0		License Plate Brackets/Light (Condition and operation)	
		_	60 61	. Fuel Door/Cap (Fuel door and cap operation—if applicable)	0 0
Comments:			01.	. Taci 2001/Cap (Luei door and cap operation—il applicable)	0 0
			1	Comments:	



Under Hood/Fluids		MEETS STANDARDS:	YES NO N	Bra	akes/Wheels/Ti	res (Cont.)		MEETS STANDARDS:	YES N	O N/
62. Hood Support/Prop Rod (Condition-holds hood up)		0 0 0		Wheel (Check cond Tire (Uneven wear, r				0 0) C	
64. Engine (Condition, oper 65. Transmission Mount (Co	ation, fluid level and le	eaks)	0 0 0		width, sidewall crac				0 0	o c
66. Transmission (Operation 67. Clutch Master Cylinder (n-MT or AT , fluid level	, hoses and leaks)	0 0 0	95.	t-Rear Brake Pad/Shoe (Re					
68. Brake Master Cylinder/B	ooster (Fluid level and	d leaks)	0 0 0	96.	of minimum thickne Rotor/Drum (Replac	e if damaged ar	nd/or wear is	s beyond service		
69. Brake System (Operation 70. 12-Volt Battery (Condition 70.	on and load test)		0 0 0	Rec	limits)ord Measurements Be				0 0	ם כ
71. Alternator (Belt conditio72. Water Pump (Noise and	leaks)		0 0 0		BRAKE PAD/SHOE	BRAKE F	ROTOR	BRAKE DRU	М	
73. Fuel Injectors (Condition 74. Radiator (Fluid level, leal					6 mm		mm			nm
75. Coolant Recovery Tank (76. Coolant Hoses (Condition						9		NA		
77. A/C Condenser (Corrosi 78. A/C Compressor (Prope	on and damage)		0 0 0	97.	Wheel (Check cond Tire (Uneven wear, 1				0 0	ם כ
79. Power Steering (Belt con	dition, tension, fluid l	evel and leaks)	0 0 0		width, sidewall crac ht-Rear				0 0) C
80. Differential Fluid (Check 81. Washer Fluid (Check lev	el and leaks)		0 0 0	99.	Brake Pad/Shoe (Rep				0 0	, c
82. Hydraulic Hose/Line (Cra	acks, kinks, loose bolt	s and leaks)	0 0 0	100	of minimum thicknes). Rotor/Drum (Replac	e if damaged ar	nd/or wear is	s beyond service		
Comments:				Rec	limits) cord Measurements B					י כ
					BRAKE PAD/SHOE	BRAKE F	ROTOR	BRAKE DRU	М	
Under Vehicle					6 _{mm}	9	mm	NA		nm
83. Brake Calipers (Evidence	e of binding, loose bo	MEETS STANDARDS:								
84. Suspension (Loose bolts 85. Universal/CV Joint/Boot				400	. Wheel (Check cond ?. Tire (Uneven wear, r				0 (ם כ
86. Exhaust System (Leaks, I					width, sidewall crac	king/cuts, adjus	t tire pressu	re)	0 0	ם כ
					BRAKE PAD/SHOE	BRAKE F	ROTOR	BRAKE DRU	М	
Comments:										
Comments:					mm		mm		m	nm
				103	. Spare Tire/Tool Kit/		(Check cond			
Brakes/Wheels/Tires	S	MEETS STANDARDS:	YES NO N		mm		(Check cond			
Brakes/Wheels/Tires Left-Front 87. Brake Pad/Shoe (Replace	e if damaged and/or v	vear exceeds 50%		Co	. Spare Tire/Tool Kit/		(Check cond			
Brakes/Wheels/Tires	e if damaged and/or v	vear exceeds 50%	0 0 0	Co	mm . Spare Tire/Tool Kit/ tools present)		(Check cond			
Brakes/Wheels/Tires Left-Front 87. Brake Pad/Shoe (Replace of minimum thickness)	e if damaged and/or v ed and/or wear is bey	vear exceeds 50%	0 0 0	Co	. Spare Tire/Tool Kit/ tools present)		(Check cond			
Brakes/Wheels/Tires Left-Front 87. Brake Pad/Shoe (Replace of minimum thickness) 88. Rotor (Replace if damage	e if damaged and/or v ed and/or wear is bey	vear exceeds 50%	0 0 0	Co	. Spare Tire/Tool Kit/tools present)	s	(Check conc	MEETS STANDARDS:	O C	10 N/
Brakes/Wheels/Tires Left-Front 87. Brake Pad/Shoe (Replace of minimum thickness) 88. Rotor (Replace if damage Record Measurements Belov	e if damaged and/or v ed and/or wear is bey	vear exceeds 50% ond service limits)	0 0 0	Cco Re 104	. Spare Tire/Tool Kit/ tools present)	S place if dirty)	(Check conc	MEETS STANDARDS:	YES N	40 N/
Brakes/Wheels/Tires Left-Front 87. Brake Pad/Shoe (Replace of minimum thickness) 88. Rotor (Replace if damage Record Measurements Below BRAKE PAD/SHOE 6	e if damaged and/or v ed and/or wear is bey w in Millimeters	ond service limits) BRAKE ROTOR 25	mm	Re 104 105	. Spare Tire/Tool Kit/tools present)	S place if dirty)	(Check conc	MEETS STANDARDS:	YES N	40 N/
Brakes/Wheels/Tires Left-Front 87. Brake Pad/Shoe (Replace of minimum thickness) 88. Rotor (Replace if damage Record Measurements Below BRAKE PAD/SHOE 6 89. Wheel (Check condition 90. Tire (Uneven wear, minimum thickness)	e if damaged and/or ved and/or wear is beyon in Millimeters mm n, lug nut, torque and mum tread depth 4/32	wear exceeds 50% ond service limits) BRAKE ROTOR 25 valve stem)	mm	Re 104 105	. Spare Tire/Tool Kit/tools present)	S place if dirty)	(Check conc	MEETS STANDARDS:	YES N	40 N/
Brakes/Wheels/Tires Left-Front 87. Brake Pad/Shoe (Replace of minimum thickness) 88. Rotor (Replace if damage Record Measurements Below BRAKE PAD/SHOE 6 89. Wheel (Check condition 90. Tire (Uneven wear, minimudth, sidewall cracking Right-Front	e if damaged and/or ved and/or wear is beyon in Millimeters mm In lug nut, torque and mum tread depth 4/32/cuts, adjust tire press	wear exceeds 50% ond service limits) BRAKE ROTOR 25 valve stem)	mm	Re 104 105	. Spare Tire/Tool Kit/tools present)	S place if dirty)	(Check conc	MEETS STANDARDS:	YES N	40 N/
Brakes/Wheels/Tires Left-Front 87. Brake Pad/Shoe (Replace of minimum thickness) 88. Rotor (Replace if damage) Record Measurements Below BRAKE PAD/SHOE 6 89. Wheel (Check condition of the condition of minimum thickness) 81. Brake Pad/Shoe (Replace of minimum thickness)	e if damaged and/or ved and/or wear is beyon in Millimeters mm n, lug nut, torque and mum tread depth 4/32 c/cuts, adjust tire pressure if damaged and/or wear in the second in the se	wear exceeds 50% ond service limits) BRAKE ROTOR 25 valve stem)		Re 104 105 Cc	. Spare Tire/Tool Kit/tools present)	place if dirty) e if dirty)	(Check conc	MEETS STANDARDS:	YES N C C C C C C C C C C C C C C C C C C	N/O N/
Brakes/Wheels/Tires Left-Front 87. Brake Pad/Shoe (Replace of minimum thickness) 88. Rotor (Replace if damage Record Measurements Below BRAKE PAD/SHOE 6 89. Wheel (Check condition 90. Tire (Uneven wear, minimudth, sidewall cracking Right-Front 91. Brake Pad/Shoe (Replace)	e if damaged and/or ved and/or wear is beyon in Millimeters mm In, lug nut, torque and second depth 4/32 colors, adjust tire pressure if damaged and/or wear is beyone ded and/or wear is beyone ded and/or wear is beyone	wear exceeds 50% ond service limits) BRAKE ROTOR 25 valve stem)		Re 104 105 Cc	. Spare Tire/Tool Kit/tools present)	place if dirty) e if dirty)e	(Check conc	MEETS STANDARDS:	YES N YES N	NO N/
Brakes/Wheels/Tires Left-Front 87. Brake Pad/Shoe (Replace of minimum thickness) 88. Rotor (Replace if damage) Record Measurements Below BRAKE PAD/SHOE 6 89. Wheel (Check condition 90. Tire (Uneven wear, minimum width, sidewall cracking) Right-Front 91. Brake Pad/Shoe (Replace of minimum thickness) 92. Rotor (Replace if damage) Record Measurements Below	e if damaged and/or ved and/or wear is beyon in Millimeters mm In, lug nut, torque and second depth 4/32 colors, adjust tire pressure if damaged and/or wear is beyone ded and/or wear is beyone ded and/or wear is beyone	wear exceeds 50% ond service limits) BRAKE ROTOR 25 valve stem)		Re 1044 105	. Spare Tire/Tool Kit/ tools present) placement Item . Engine Air Filter (Re . Cabin Filter (Replacements: ad Test . Engine Operation (Control of the control of	place if dirty)e if dirty)e if dirty)	nd low spee	MEETS STANDARDS:	YES N () () () () () () () () () (
Brakes/Wheels/Tires Left-Front 87. Brake Pad/Shoe (Replace of minimum thickness) 88. Rotor (Replace if damage) Record Measurements Below BRAKE PAD/SHOE 6 89. Wheel (Check condition 90. Tire (Uneven wear, minimum width, sidewall cracking) Right-Front 91. Brake Pad/Shoe (Replace of minimum thickness) 92. Rotor (Replace if damage) Record Measurements Below BRAKE PAD/SHOE	e if damaged and/or ved and/or wear is beyon in Millimeters mm n, lug nut, torque and very mum tread depth 4/32 veuts, adjust tire pressue if damaged and/or wear is beyon in Millimeters	wear exceeds 50% ond service limits) BRAKE ROTOR 25 valve stem)	mm 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Re 1044 1055 Ca Ro 1066 1077 1088 1099 110	. Spare Tire/Tool Kit/ tools present) placement Item . Engine Air Filter (Re . Cabin Filter (Replacements: ad Test . Engine Operation (C .MT Clutch (Smoothn . Braking System (No . Cruise Control Syste . Steering/Tire/Whee	place if dirty) e if dirty) e if dirty) cold/hot/high a ess, effort and s ise, vibration an em (Engage, can	nd low spee slippage) d effort) cel and resu	MEETS STANDARDS: MEETS STANDARDS ds)	YES N () () () () () () () () () (
Brakes/Wheels/Tires Left-Front 87. Brake Pad/Shoe (Replace of minimum thickness) 88. Rotor (Replace if damage) Record Measurements Below BRAKE PAD/SHOE 6 89. Wheel (Check condition 90. Tire (Uneven wear, minimum width, sidewall cracking) Right-Front 91. Brake Pad/Shoe (Replace of minimum thickness) 92. Rotor (Replace if damage) Record Measurements Below	e if damaged and/or ved and/or wear is beyon in Millimeters mm In, lug nut, torque and second depth 4/32 colors, adjust tire pressure if damaged and/or wear is beyone ded and/or wear is beyone ded and/or wear is beyone	wear exceeds 50% ond service limits) BRAKE ROTOR 25 valve stem)		Re 104 105 Co 106 107 108 109 110 111.	. Spare Tire/Tool Kit/tools present)	place if dirty) e if dirty) e if dirty) ess, effort and sise, vibration anem (Engage, can I (Abnormal vib	nd low spee slippage) d effort) cel and resu ration and st	MEETS STANDARDS: MEETS STANDARDS ds)	YES N O C C C C C C C C C C C C C C C C C C	10 N/A
Brakes/Wheels/Tires Left-Front 87. Brake Pad/Shoe (Replace of minimum thickness) 88. Rotor (Replace if damage) Record Measurements Below BRAKE PAD/SHOE 6 89. Wheel (Check condition 90. Tire (Uneven wear, minimum width, sidewall cracking) Right-Front 91. Brake Pad/Shoe (Replace of minimum thickness) 92. Rotor (Replace if damage) Record Measurements Below BRAKE PAD/SHOE	e if damaged and/or ved and/or wear is beyon in Millimeters mm n, lug nut, torque and very mum tread depth 4/32 veuts, adjust tire pressue if damaged and/or wear is beyon in Millimeters	wear exceeds 50% ond service limits) BRAKE ROTOR 25 valve stem)	mm 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Re 1044 1055 Ca Ro 1066 1077 1088 1099 110 111. 112	. Spare Tire/Tool Kit/tools present)	place if dirty) e if dirty) e if dirty) ess, effort and sise, vibration anem (Engage, can I (Abnormal vib	nd low spee slippage) d effort) cel and resu ration and st	MEETS STANDARDS: MEETS STANDARDS ds)	YES N O C C C C C C C C C C C C C C C C C C	10 N//



Technician Acknowledgment (Signature Required)

I certify that: i) I inspected all applicable items on this checklist; ii) all required reconditioning was performed and meets Honda Certified Pre-Owned Vehicle Program Standards for HondaTrue Used vehicles; and iii) this vehicle is eligible for certification as a HondaTrue Used vehicle. All items that did **not** meet program standards have been properly repaired with Honda Genuine Parts and thoroughly documented on the reconditioning repair order. All diagnostic trouble codes (DTCs) have been remedied and cleared, and all applicable campaigns and recalls have been properly completed prior to vehicle certification and delivery.

100

Technician	FRANCISCO PASSOS	DPTS #: 	Signature:	Date: 10/27/2025
Dealer I	Management Ackno	wledgment (Signature Require	d)	
I certify that Program St	at: i) all applicable items on t	his checklist were inspected; ii) all require	d reconditioning was performed and meets l r certification as a HondaTrue Used vehicle a	Honda Certified Pre-Owned Vehicle ınd will be reported to American Honda
Name (Prin	t): MICHAEL ROBITAILLE	Signa	ature:	Date: 10/28/2025
Please sele	ect your title:			
Dealer P	rincipal	Dealership Manager	General Manager	General Sales Manager
□ Sales Ma	anager	Business Office Manager	Service Manager	Pre-Owned Manager
Certifie	d Program Standard	S		
• All fluids	all required maintenance must be topped off nust be same size, brand, loa	ad, speed rating and free of damage	 OEM or non-OEM windshields contain and impairment of the driver's line of si If a windshield cannot be repaired, it no OEM or comparable aftermarket wind 	ght must be repaired and/or replaced. nust be replaced with either Honda
Docume	entation/Keys/Manu	MEETS STANDARDS: YES NO N/A		MEETS STANDARDS: YES NO N/A
A. Vehicle B. Vehicle C. Owner' D. Owner' Paper	History Report (CARFAX™ cs Guides Manual	r AutoCheck*)	Check items provided to the customer of G. Navigation Code #: ()
Paper	O CD/DVD O			
F. Certifie Paper	d Warranty Booklet CD/DVD O	nline		
All applica	ble items checked above (A	(Signature Required) through J) have been reviewed with and p	rovided to me by the dealership at the time o	·
Customer	Name (Print):		_ Signature:	Date: