

Dealer	Name:	SCOTT HONDA OF VINELAND
Dealer #	208957	

#### **Vehicle Information**

 Year:
 2019
 Model:
 CR-V
 VIN:
 7FARW2H81KE008144

 Mileage:
 21938
 Color:
 MODERN STEEL METALLIC

 Stock #:
 \$5607
 Repair Order #:
 605924





VIN Verification		Eligible	Not Eligible	VEHICLES REPORTED WITH THE FOLLOWING ARE <b>NOT</b> ELIGIBLE FOR CERTIFICA	ATION
1. Vehicle History Report (VHR cannot have any conditions listed on the	right	:) 0	0	- Odometer Rollback - Hail/Fire/Flood Damage	
2. VIN Status Inquiry (All open campaigns/recalls must be completed)	)	0	0	- Not Actual Mileage - Dismantled/Reconstructed	
3. VIN Plates (All VIN plates must match engine compartment,				- Exceeds Mechanical Limits - Branded/Junked/Salvaged Title	
doorjamb and dash)		0	0	- Manufacturer Buyback - Airbag Deployment/Gray Market	
Unibody		Eligible	Not Eligible	VEHICLES WITH UNIBODY DAMAGE ARE <b>NOT</b> ELIGIBLE FOR CERTIFICATION:	
4. Frame (Carefully inspect the vehicle for any prior structural damage	e)	0	0	Report any visible signs of unibody damage to the Service Manager.	
Vehicle Diagnostics			Not	VEHICLES WITH AFTER-MARKET ITEMS ARE <b>NOT</b> ELIGIBLE FOR CERTIFICATIO	
5. Check for Diagnostic Trouble Codes (DTC)		Eligible	Eligible		
5. Check for Diagnostic frouble Codes (DTC)		. U	0	Refer to the certified program standards on page 4 of this checklist.	
Front Interior MEETS STANDARDS:	YES N	IO N/A	Re	ear Interior MEETS STANDARDS: YES	NO N/A
6. Key Remotes, at least one (Unlock, lock and panic buttons)	0 (	<b>0</b>	40	. Seats (Upholstery condition, operation and tracks)	0 0
7. Keyless Entry System (Driver's-door button-unlock/lock)				. Seat Belts (Belts, buckles, latches, anchors and retraction)	
8. SRS Airbags (Exterior condition/Check warning lamp self-check)	0 (	<b>-</b>	42	. Head Restraints (Present & Adjustable up/down)	0 0
9. Ignition Switch/Engine Start Button (Engine starts)	0 0	<b>0</b>		. Windows (Operation-noise, speed, full travel and glass)	<b>O</b> O
10. Instrument Panel Operation (Temp, fuel, speedometer gauge/All			44	. Rear/Sliding Doors (Operation, trim, panels, handles, latches,	
indicators illuminate "ON" position)				locks)	0 0
11. Dash (Condition, instrument panel, light and brightness)	0 0	0	45	. Cargo Light (Condition and operation) $\ \square$	0 0
12. Horn (Operation)					$\overline{}$
13. Steering Wheel (Condition, tilt, telescopic and lock mode)			C	Comments:	
14. Steering Wheel-Mounted Controls (Operation)					
15. Windshield Wipers/Washers (Aim, pressure–front/rear)					
16. Shifter (Check all shifting points–MT or AT)			_		
18. Hood Release (Operation)		0	Е.	and Francisco	
19. Trunk/Tailgate/Hatch Release (Operation)				ont Exterior MEETS STANDARDS: YES	
20. Fuel Door Release (Operation)				. Windshield Glass (Cracks, chips, pits, scratches, antenna)	<b>O</b> O
21. Seats (Operation and tracks)			47.	. Windshield Wiper Blades/Arms (Condition and high-/low-speed	
22. Seat Heaters (Operation and heating performance)				operation)	
23. Seat Belts (Belts, buckles, latches and retraction)	0 (	<b>o</b>		Headlights/Lenses (Condition and operation-moisture)	
24. Head Restraints (Present & Adjustable up/down)				Fog Lights/Lenses (Condition and operation)	
25. Windows (Operation-noise, speed, full travel and glass)				Daytime Running Lights/Lenses (Condition and operation)	
26. Front Doors (Operation, trim, panels, handles, latches, locks)	0 0	<b>-</b>	51.	. Turn Signal Lights/Lenses (Condition and operation)	0 0
27. Side Mirrors (Condition, operation, side-view camera–					$\overline{}$
if applicable)			C	Comments:	
28. Rearview Mirror (Operation, auto-dimming-if equipped)					
29. Sunroof/Shade/Glass (Condition and operation)					
30. Sun Visors/Mirrors (Condition-flip up, down/sideways)			_		
31. Interior Lights (Condition and operation)			D	ear Exterior MEETS STANDARDS: YES	
33. Audio System AM/FM/SXM/CD Radio (Operation, display, control	0 (	<u>,</u> 0	κe	ear Exterior MEETS STANDARDS: YES	NO N/A
panel, speakers)	0.0				0 0
34. Intelligent Multi-Information Display (Operation and display)				. Windshield Wiper Blade/Arm (Condition and operation)	0 0
35. Bluetooth* HandsFreeLink* (Perform voice commands—must pair					0 0
with phone)	0 0	0		. Taillights/Lenses (Condition and operation-moisture)	
36. Navigation System (Operation, display, clear all stored data)			56	Backup Lights/Lenses (Condition and operation)	0 0
37. Rearview Camera (Operation and display)			57.	. Turn Signal Lights/Lenses (Condition and operation)	0 0
38. Alarm/Theft-Deterrent System	0 (	<b>o</b>	58	Emergency Lights/Lenses (Condition and operation)	0 0
39. Cigarette Lighter/Power Outlets (if equipped)	0 0	0		License Plate Brackets/Light (Condition and operation)	
		_	60 61	. Fuel Door/Cap (Fuel door and cap operation—if applicable)	0 0
Comments:			01.	. Taci 2001/Cap (Luei door and cap operation—il applicable)	0 0
			1	Comments:	



Under Hood/Fluids		MEETS STANDARDS:	YES NO N/	Bra	akes/Whe	eels/Tire	es (Cont.)		MEETS STANDARDS:	YES N	O N/
62. Hood Support/Prop Rod (Condition-holds hood up)						on, lug nut, torqu nimum tread dep		alve stem)	0 (	<b>)</b> C	
		0 0 0		width, side				ire)	0 0	<b>)</b> C	
		0 0 0						ear exceeds 50%			
68. Brake Master Cylinder/I	Booster (Fluid level ar	nd leaks)	0 0 0	96.	Rotor/Drur	n (Replace	if damaged and/	or wear i	s beyond service		
69. Brake System (Operation 70. 12-Volt Battery (Condition 12)	ion and load test)		O O C	Rec					/A if not applicable	0 (	ם כ
<ul><li>71. Alternator (Belt condition</li><li>72. Water Pump (Noise and</li></ul>	l leaks)		O O C		BRAKE PAD/	SHOE	BRAKE ROT	OR	BRAKE DRU	М	
73. Fuel Injectors (Condition 74. Radiator (Fluid level, lea								mm			
<ul><li>75. Coolant Recovery Tank</li><li>76. Coolant Hoses (Conditi</li></ul>					9.0	mm	10.0	mm	N/A	- ''	nm
77. A/C Condenser (Corros 78. A/C Compressor (Prope	sion and damage)		O O C				on, lug nut, torqı nimum tread der		alve stem)	0 (	ם כ
79. Power Steering (Belt co	ndition, tension, fluid	level and leaks)	0 0 0		width, side				ıre)	0 (	<b>)</b> C
<ul><li>80. Differential Fluid (Chec</li><li>81. Washer Fluid (Check lev</li></ul>	vel and leaks)		O O C	99.	ht-Rear Brake Pad/S	hoe (Repla	ce if damaged ar	nd/or we	ar exceeds 50%		
82. Hydraulic Hose/Line (Ci	racks, kinks, loose bol	ts and leaks)	0 0 0		). Rotor/Drur	m (Replace	if damaged and/	or wear i	s beyond service	0 (	
Comments:				Rec					/A if not applicable	0 (	ם כ
					BRAKE PAD/		BRAKE ROT		BRAKE DRU	M	
Under Vehicle					9.0	mm	10.0	mm	N/A		nm
83. Brake Calipers (Evidence	ce of binding, loose b	MEETS STANDARDS:									
84. Suspension (Loose bolt 85. Universal/CV Joint/Boo							on, lug nut, torqı nimum tread der		llve stem) across tread	0 (	ם כ
86. Exhaust System (Leaks,					width, side	wall cracki	ng/cuts, adjust ti	re pressu	ıre)	0 (	<b>)</b> C
						CHOE	22445 207	· O D	DDAKE DDI		
Comments:					BRAKE PAD/	SHUE	BRAKE ROT	OK	BRAKE DRU	М	
Comments:					BRAKE PAD/	mm	BRAKE ROT	mm	BRAKE DRU		nm
				103	. Spare Tire/	mm /Tool Kit/Ti	re Repair Kits (Ch	mm neck con	ditions and all	n	
Brakes/Wheels/Tire	es	MEETS STANDARDS:	YES NO N/		. Spare Tire/	mm /Tool Kit/Ti	re Repair Kits (Ch	mm neck con		n	
Brakes/Wheels/Tire Left-Front 87. Brake Pad/Shoe (Replace	ce if damaged and/or	wear exceeds 50%		_	. Spare Tire/	mm /Tool Kit/Ti	re Repair Kits (Ch	mm neck con	ditions and all	n	
Brakes/Wheels/Tire	ce if damaged and/or	wear exceeds 50%	0 0 0	_	. Spare Tire/ tools prese	mm /Tool Kit/Ti	re Repair Kits (Ch	mm neck con	ditions and all	n	
Brakes/Wheels/Tire Left-Front 87. Brake Pad/Shoe (Replacof minimum thickness).	ce if damaged and/or ged and/or wear is be	wear exceeds 50%	0 0 0	Со	. Spare Tire/ tools prese mments:	mm /Tool Kit/Ti ent)	re Repair Kits (Ch	mm neck con	ditions and all	n	
Brakes/Wheels/Tire Left-Front 87. Brake Pad/Shoe (Replace of minimum thickness). 88. Rotor (Replace if damage)	ce if damaged and/or ged and/or wear is be ow in Millimeters	wear exceeds 50%	0 0 0	Co	. Spare Tire/ tools prese mments:	/Tool Kit/Ti	re Repair Kits (Ch	mm neck con	ditions and all	YES N	10 N/
Brakes/Wheels/Tire Left-Front 87. Brake Pad/Shoe (Replace of minimum thickness). 88. Rotor (Replace if damage Record Measurements Below	ce if damaged and/or ged and/or wear is be ow in Millimeters	wear exceeds 50% yond service limits)	0 0 0	Re 104	. Spare Tire/tools prese	/Tool Kit/Tient)nt ltems	re Repair Kits (Ch	mm neck con	ditions and all	YES N	10 N/
Brakes/Wheels/Tire Left-Front 87. Brake Pad/Shoe (Replace of minimum thickness). 88. Rotor (Replace if damage Record Measurements Beloe	ged and/or wear is begow in Millimeters	yond service limits)  BRAKE ROTOR  25.0	mm	Re 104 105	. Spare Tire/tools prese	/Tool Kit/Tient)nt ltems	re Repair Kits (Ch	mm neck con	ditions and all	YES N	40 N/
Brakes/Wheels/Tire Left-Front 87. Brake Pad/Shoe (Replace of minimum thickness). 88. Rotor (Replace if damage Record Measurements Below BRAKE PAD/SHOE 9.0  89. Wheel (Check condition 90. Tire (Uneven wear, minimum thickness).	ged and/or wear is begow in Millimeters  mm  m, lug nut, torque and imum tread depth 4/3	wear exceeds 50% yond service limits)  BRAKE ROTOR  25.0  I valve stem)	mm	Re 104 105	. Spare Tire/tools presented in the second presented i	/Tool Kit/Tient)nt ltems	re Repair Kits (Ch	mm neck con	ditions and all	YES N	40 N/
Brakes/Wheels/Tire Left-Front 87. Brake Pad/Shoe (Replace of minimum thickness). 88. Rotor (Replace if damage Record Measurements Below BRAKE PAD/SHOE  9.0  89. Wheel (Check conditions). Tire (Uneven wear, min width, sidewall cracking Right-Front	ged and/or wear is begow in Millimeters  mm  an, lug nut, torque and imum tread depth 4/3 g/cuts, adjust tire pres	wear exceeds 50% yond service limits)  BRAKE ROTOR  25.0  I valve stem)	mm	Re 104 105	. Spare Tire/tools presented in the second presented i	/Tool Kit/Tient)nt ltems	re Repair Kits (Ch	mm neck con	ditions and all	YES N	40 N/
Brakes/Wheels/Tire Left-Front 87. Brake Pad/Shoe (Replace of minimum thickness). 88. Rotor (Replace if damage Record Measurements Below BRAKE PAD/SHOE  9.0  89. Wheel (Check condition 90. Tire (Uneven wear, min width, sidewall cracking Right-Front 91. Brake Pad/Shoe (Replace of minimum thickness)	mm  on, lug nut, torque and imum tread depth 4/3 g/cuts, adjust tire presence if damaged and/or	wear exceeds 50%  yond service limits)  BRAKE ROTOR  25.0  I valve stem)	mm	Re 104 105 Cc	. Spare Tire/tools prese	/Tool Kit/Tient)	re Repair Kits (Ch	mm neck cond	MEETS STANDARDS	YES N	N/O N/
Brakes/Wheels/Tire Left-Front 87. Brake Pad/Shoe (Replace of minimum thickness). 88. Rotor (Replace if damage Record Measurements Below BRAKE PAD/SHOE 9.0  89. Wheel (Check condition) 70. Tire (Uneven wear, min width, sidewall cracking Right-Front) 91. Brake Pad/Shoe (Replace)	mm  on, lug nut, torque and imum tread depth 4/3 g/cuts, adjust tire presence if damaged and/or wear is begad and/	wear exceeds 50%  yond service limits)  BRAKE ROTOR  25.0  I valve stem)	mm	Re 104 105 Cc	. Spare Tire/tools prese	mm /Tool Kit/Tient)	re Repair Kits (Chace if dirty)f dirty)f	neck con	MEETS STANDARDS	YES N O ( O ( O ( O ( O ( O ( O ( O ( O ( O	10 N/
Brakes/Wheels/Tire Left-Front 87. Brake Pad/Shoe (Replace of minimum thickness). 88. Rotor (Replace if damage Record Measurements Below BRAKE PAD/SHOE  9.0  89. Wheel (Check condition 90. Tire (Uneven wear, min width, sidewall cracking Right-Front 91. Brake Pad/Shoe (Replace of minimum thickness) 92. Rotor (Replace if damage Record Measurements Below)	mm  on, lug nut, torque and imum tread depth 4/3 g/cuts, adjust tire presence if damaged and/or wear is become in Millimeters	wear exceeds 50% yond service limits)  BRAKE ROTOR  25.0  I valve stem)	mm	Re 104 105 Cc Ro 106 107. 108	. Spare Tire/ tools prese mments:  placeme . Engine Air . Cabin Filte mments:  ad Test . Engine Op .MT Clutch ( . Braking Sys	mm  /Tool Kit/Ti ent)  nt Items  Filter (Replace in the continuous of the con	re Repair Kits (Chace if dirty)f dirty)f dirty) and ss, effort and slipe, vibration and e	low speepage)	MEETS STANDARDS  MEETS STANDARDS	YES N YES N O ( O ( O ( O ( O ( O ( O ( O ( O ( O	
Brakes/Wheels/Tire Left-Front 87. Brake Pad/Shoe (Replace of minimum thickness). 88. Rotor (Replace if damage Record Measurements Below BRAKE PAD/SHOE  9.0  89. Wheel (Check condition 90. Tire (Uneven wear, min width, sidewall cracking Right-Front 91. Brake Pad/Shoe (Replace of minimum thickness) 92. Rotor (Replace if damage Record Measurements Below BRAKE PAD/SHOE	mm  on, lug nut, torque and imum tread depth 4/3 g/cuts, adjust tire presence if damaged and/or wear is beow in Millimeters	wear exceeds 50%  yond service limits)  BRAKE ROTOR  25.0  I valve stem)	mm	Re 1044 105	. Spare Tire/ tools prese mments:  placemer . Engine Air . Cabin Filte comments:  ad Test . Engine Op .MT Clutch ( . Braking Sys Cruise Con . Steering/Ti	mm  /Tool Kit/Ti ent)	re Repair Kits (Ch	low speepage)	MEETS STANDARDS eds)	YES N ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) (	
Brakes/Wheels/Tire Left-Front 87. Brake Pad/Shoe (Replace of minimum thickness). 88. Rotor (Replace if damage Record Measurements Below BRAKE PAD/SHOE  9.0  89. Wheel (Check condition 90. Tire (Uneven wear, min width, sidewall cracking Right-Front 91. Brake Pad/Shoe (Replace of minimum thickness) 92. Rotor (Replace if damage Record Measurements Below)	mm  on, lug nut, torque and imum tread depth 4/3 g/cuts, adjust tire presence if damaged and/or wear is become in Millimeters	wear exceeds 50% yond service limits)  BRAKE ROTOR  25.0  I valve stem)	mm	Re 104 105 Cc Ro 106 107. 108 109 110. 111.	. Spare Tire/tools presented and test . Engine Air . Cabin Filte comments:  ad Test . Engine Op . MT Clutch ( . Braking System . Steering/Tic CV Joint/Dic . CV Joint/Dic . CV Joint/Dic . Steering/Tic . CV Joint/Dic .	mm  /Tool Kit/Ti ent)	ace if dirty)f dirty)	low speepage)	MEETS STANDARDS eds)	YES N ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) (	10 N/A
Brakes/Wheels/Tire Left-Front 87. Brake Pad/Shoe (Replace of minimum thickness). 88. Rotor (Replace if damage Record Measurements Below BRAKE PAD/SHOE  9.0  89. Wheel (Check condition 90. Tire (Uneven wear, min width, sidewall cracking Right-Front 91. Brake Pad/Shoe (Replace of minimum thickness) 92. Rotor (Replace if damage Record Measurements Below BRAKE PAD/SHOE	mm  on, lug nut, torque and imum tread depth 4/3 g/cuts, adjust tire presence if damaged and/or wear is beow in Millimeters	wear exceeds 50%  yond service limits)  BRAKE ROTOR  25.0  I valve stem)	mm	Re 1044 1055 Ccc Ro 1066 1077 1088 1099 110. 111. 112.	. Spare Tire/tools presented and test . Engine Air . Cabin Filte comments:  ad Test . Engine Op . MT Clutch ( . Braking System . Steering/Tic CV Joint/Dic . CV Joint/Dic . CV Joint/Dic . Steering/Tic . CV Joint/Dic .	mm  /Tool Kit/Ti ent)	ace if dirty)f dirty)	low speepage)	MEETS STANDARDS eds)	YES N ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) (	10 N/A



#### Technician Acknowledgment (Signature Required)

I certify that: i) I inspected all applicable items on this checklist; ii) all required reconditioning was performed and meets Honda Certified Pre-Owned Vehicle Program Standards for HondaTrue Used vehicles; and iii) this vehicle is eligible for certification as a HondaTrue Used vehicle. All items that did **not** meet program standards have been properly repaired with Honda Genuine Parts and thoroughly documented on the reconditioning repair order. All diagnostic trouble codes (DTCs) have been remedied and cleared, and all applicable campaigns and recalls have been properly completed prior to vehicle certification and delivery.

Technician: DANIEL WEIGEL	DPTS #: <b></b>	Signature:	Date: 7/2/2025
I certify that: i) all applicable items on t		d reconditioning was performed and meets I r certification as a HondaTrue Used vehicle a	
Name (Print): MICHAEL CAFARELLI	Signa	ture:	Date:
Please select your title:			
Dealer Principal	<ul><li>Dealership Manager</li></ul>	<ul><li>General Manager</li></ul>	<ul> <li>General Sales Manager</li> </ul>
□ Sales Manager	<ul><li>Business Office Manager</li></ul>	Service Manager	Pre-Owned Manager
Perform all required maintenance     All fluids must be topped off     All tires must be same size, brand, loa	d, speed rating and free of damage	<ul> <li>OEM or non-OEM windshields contain and impairment of the driver's line of si If a windshield cannot be repaired, it n OEM or comparable aftermarket wind</li> </ul>	ght must be repaired and/or replaced. nust be replaced with either Honda shield
Documentation/Keys/Manua			MEETS STANDARDS: YES NO N/A
B. Vehicle History Report (CARFAX™ of C. Owner's Guide	AutoCheck*)	Check items provided to the customer of G. Navigation Code #: (	)
E. New Car Warranty Manual  Paper CD/DVD Or	o o o	Comments:	
F. Certified Warranty Booklet Paper CD/DVD Or	lline		
Customer Acknowledgment All applicable items checked above (A		rovided to me by the dealership at the time o	of vehicle delivery.
Customer Name (Print):		_ Signature:	Date: